



Seasonal Flood Protection Maintenance Record- 20____

Place your initials in the appropriate box to record activities completed per season.

| Outside the Home | | | | | | |
|---------------------------------------------------------------------------------------------------------------------------------------------|----------|--------|------|--------|--|--|
| Maintenance Activity | Spring | Summer | Fall | Winter | | |
| 1. Remove debris as needed from ne storm drain or municipal drainag Notify local authority if water is n draining within 24 hours. | e ditch. | | | | | |
| 2. Maintain grading within 1.8m (6') home so that water flows away fro foundation. | | | | × | | |
| 3. Remove debris as needed from ea troughs and downspouts. | ves | | | × | | |
| 4. Extend downspouts and sump pur discharge pipes at least 1.8m (6') from foundation or to nearest dra swale. | away | | | | | |
| 5. Clear snow away 1.8m (6') from foundation. | × | * | * | | | |
| Seal cracks and gaps in basement windows and frames. Repair or re as needed. | place | | | × | | |
| 7. Remove debris and snow from wi wells. | ndow | | | | | |
| 8. Seal cracks and gaps in exterior d and frames. Repair or replace as r | | | | | | |
| 9. Remove debris from all exterior d (e.g. located in front of garage doo below grade doors). | | | | | | |





| 10. Test exterior drains. Clear, repair or replace as needed. | | | | × | | |
|-------------------------------------------------------------------------------------------------------------|--------|--------|------|--------|--|--|
| 11. Seal cracks and gaps in foundation. | | | | * | | |
| 12. Repair leaks in hose bib(s). | | | | * | | |
| 13. Turn off exterior water supply and drain pipes and hoses before freeze up. Remove and store hose. | * | × | | × | | |
| Inside the Home | | | | | | |
| Maintenance Activity | Spring | Summer | Fall | Winter | | |
| 14. Test sump pump, backup sump pump, backup battery, and alarm. Clean, repair or replace as needed. | | | | | | |
| 15. Test backwater valve and alarm. Clean, repair or replace as needed. | | | | | | |
| 16. Remove items blocking water drainage pathway to floor drain. | | | | | | |
| 17. Test floor drain. Clear, repair or replace as needed. | | | | | | |
| 18. Check pipes and appliances for leaks or deterioration. Repair or replace as needed. | | | | | | |
| 19. Remove valuables from basement or store in watertight containers elevated from floor. | | | | | | |